



Concrete Admixtures and Fiber

## LUBRIBLOCK

Admixture and Release Agent for Block and Architectural Concrete Products

### DESCRIPTION

**LUBRIBLOCK** is an admixture and form release which is synthetically produced and formulated specifically for use in concrete block, precast, paver products and architectural concrete products. **LUBRIBLOCK** is ideal for situations where a liquid plasticizer is desired or necessary to reduce efflorescence, increasing water tightness, improve appearance, moldability and early age strengths.

### USES

- Concrete block
- Architectural concrete panels
- Pavers
- Precast concrete
- Roof tiles
- Form release for steel forms

### ADVANTAGES

- Improved appearance and texture
- Minimizes efflorescence
- Lowers moisture absorption
- Increased water tightness
- Higher strengths at all ages
- Increased production and reduced wear on molds and equipment
- Contains plasticizers for easy stripping and increased production

### APPLICATION

**LUBRIBLOCK** is a highly concentrated liquid that should be mixed with 20 parts of water to one part of **LUBRIBLOCK**. Stir well. After solution is prepared, use at a rate of 3 to 8 ounces per 100 lb (375 to 750 ml per 100 kg ) of cement.

## INTERNATIONAL MATERIALS INDUSTRIES, L.L.C.

2800 N. Johnson St \* New Orleans, Louisiana 70117 \* PHONE: (504) 267-3344 \* Fax: (504) 267-3345

The information herein is to assist customers in determining whether our products are suitable for their applications. Our products are intended for sale to industrial and commercial customers. We request that customers inspect and test our products before use and satisfy themselves as to contents and suitability, nothing herein shall constitute a warranty, express or implied, including any warranty of merchantability or fitness, nor is protection from any law or patent to be inferred. All patent rights are reserved. The exclusive remedy for all proven claims is replacement of our materials and in no event shall we be liable for special, incidental or consequential damages.

## APPLICATION AS A STEEL FORM RELEASE AGENT

LUBRIBLOCK is used as a steel form release diluted with 20 parts of water and one part LUBRIBLOCK . Apply in a thin uniform film with a sprayer, brush or roller. No special application equipment is necessary, but a spray application is the most practical.

Ponding or puddling is to be avoided.

Specific application rate for steel is as follows:

**24.5 m<sup>2</sup>/L (1000 ft<sup>2</sup>) per diluted gallon.**